Specifications

Photo is representative

Eaton XTCE185H22TD

Eaton XT IEC contactor, 185A, 24-27 Vdc, 2NO-2NC, 185A, Frame H, 140 mm, 50, 75, 150, 200 hp (3PH @200, 240, 480, 600 V), Three-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing contactor

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE185H22TD
EAN	4015081363186
PRODUCT LENGTH/DEPTH	6.22047244 in
PRODUCT HEIGHT	7.08661417 in
PRODUCT WIDTH	5.51181102 in
PRODUCT WEIGHT	0.61729433 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Powering Business Worldwide

Product specifications

AMPERAGE RATING	185A
HP RATING - MAX	50, 75, 150, 200 hp (3PH @200,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
TERMINALS	Screw terminals
COIL VOLTAGE	24-27 Vdc
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	185 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE185H22TD

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.