

# Specifications

## Eaton XTMFXML

Eaton motor control mechanical interlock, used with XTRM miniature control relays



### General specifications

<b>PRODUCT NAME</b>	Eaton motor control mechanical interlock
<b>CATALOG NUMBER</b>	XTMFXML
<b>EAN</b>	4015080101130
<b>PRODUCT LENGTH/DEPTH</b>	1.5 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	2 in
<b>PRODUCT WEIGHT</b>	0.09 lb
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	CCC Marked CE Marked ATEX Compliant
<b>CERTIFICATIONS</b>	IEC 60947 EN 60947 UL Listed CSA Certified
<b>CATALOG NOTES</b>	For two contactors with AC or DC operated magnet system that are horizontally mounted, the distance between contactors is 0 mm and the mechanical lifespan = $2.5 \times 10^6$ operations. Orders must be placed in multiples of package quantity listed
<b>GLOBAL CATALOG</b>	XTMFXML



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	XTRM miniature control relays
<b>TYPE</b>	Miniature Contactor Accessory - Mechanical Interlock
<b>SPECIAL FEATURES</b>	XTRM miniature control relays
<b>QUANTITY</b>	5

## Resources

CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTMCXML</a>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

