

Specifications



Photo is representative



Eaton XTMCC9A10TD

Eaton XT IEC mini contactor, 8.80A, 24 Vdc, 1NO, 20A, 45 mm mini, 0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Spring cage terminals, Full voltage non-reversing mini contactor

General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	XTMCC9A10TD
EAN	4015082301651
PRODUCT LENGTH/DEPTH	1.79 in
PRODUCT HEIGHT	2.28 in
PRODUCT WIDTH	1.44 in
PRODUCT WEIGHT	0.3 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Consult local sales office for availability.

Product specifications

AMPERAGE RATING	8.80A
HP RATING - MAX	0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing mini contactor
FRAME SIZE	45 mm - mini
TERMINALS	Spring cage terminals
COIL VOLTAGE	24 Vdc
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	20 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS

[Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1](#)

MULTIMEDIA

[S1. E4. Ask the Experts - NEMA, IEC and DP contactors](#)

[Contactors Explained](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTMCC9A10TD](#)

WARRANTY GUIDES

[Selling Policy 25-000 - Distribution and Control Products and Services](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

