

Specifications



Eaton XTCEXFAC13

Contactor Accessory - Auxiliary Contact, Four-pole, Screw terminals, 1NO-3NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

General specifications

PRODUCT NAME	Eaton motor control auxiliary contact
CATALOG NUMBER	XTCEXFAC13
EAN	4015082764258
PRODUCT LENGTH/DEPTH	2.5 in
PRODUCT HEIGHT	7.1 in
PRODUCT WIDTH	4.5 in
PRODUCT WEIGHT	0.01 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked ATEX Compliant CCC Marked
CERTIFICATIONS	IEC 60947 EN 60947 UL Listed CSA Certified
CATALOG NOTES	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.
GLOBAL CATALOG	XTCEXFAC13



Powering Business Worldwide

Product specifications

USED WITH	XTRE control relays
NUMBER OF POLES	Four-pole
TYPE	Contactors Accessory - Auxiliary Contact
TERMINALS	Screw
CONTACT CONFIGURATION	1 NO-3 NC
MOUNTING METHOD	Front
RATED OPERATIONAL CURRENT	6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
CONVENTIONAL THERMAL CURRENT	16A
QUANTITY	5

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCEXFAC13

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

