Specifications

Photo is representative

Eaton XTMC9A10E

Eaton XT IEC mini contactor, 8.80A, 208 Vac, 60 Hz, 1NO, 20A, 45 mm mini, 60 Hz, 0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing mini contactor

General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	XTMC9A10E
EAN	4015082102562
PRODUCT LENGTH/DEPTH	2.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	2.5 in
PRODUCT WEIGHT	0.5 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Powering Business Worldwide

Product specifications

AMPERAGE RATING	8.80A
HP RATING - MAX	0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing mini contactor
FREQUENCY RATING	60 Hz
TERMINALS	Screw terminals
COIL VOLTAGE	208 Vac, 60 Hz
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	20 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTMC9A10E

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.