

Specifications



Photo is representative



Eaton Y48M37T30CU

Eaton General purpose encapsulated transformer, EPT, copper, NEMA 3R, 243, 60 Hz, three-phase, 480 V, 380Y/220 V, 2 at +2.5% FCAN, 4 at -2.5% FCBN, 115 °C rise, 30 KVA, indoor-outdoor, 84A

General specifications

PRODUCT NAME	Eaton General purpose encapsulated transformer
CATALOG NUMBER	Y48M37T30CU
UPC	786685197906
PRODUCT LENGTH/DEPTH	10.52 in
PRODUCT HEIGHT	17.38 in
PRODUCT WIDTH	20 in
PRODUCT WEIGHT	595 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Copper
DESIGN	EPT
ENCLOSURE	NEMA 3R
FRAME	243
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	General-Purpose Encapsulated Transformer
WIRING CONNECTION	84A

Miscellaneous

WEATHERSHIELD	Indoor-Outdoor
----------------------	----------------

Performance Ratings

FREQUENCY RATING	60 Hz
PHASE	Three-phase
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	380Y/220 V
TEMPERATURE RISE	115 °C rise
VOLT AMPERE RATING	30 kVA

Resources

CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - Y48M37T30CU

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

