

Specifications



Eaton BR1224L200

Eaton Eaton BR main lug loadcenter, No feed-thru lugs, includes BREQS125 hold-down screw, 200 A, B2, Aluminum, NEMA 1, Metallic, 25 kAIC, BWH, Combination, 24 Circuits, Twenty-four pole, Three-wire, Single-phase, 120/240V, #1 AWG-300 kcmil Cu/Al

General specifications

| | |
|-----------------------------|--|
| PRODUCT NAME | Eaton BR main lug loadcenter |
| CATALOG NUMBER | BR1224L200 |
| UPC | 786676447300 |
| PRODUCT LENGTH/DEPTH | 3.88 in |
| PRODUCT HEIGHT | 18.75 in |
| PRODUCT WIDTH | 14.31 in |
| PRODUCT WEIGHT | 15.8 lb |
| WARRANTY | 10 year |
| CERTIFICATIONS | UL 67 UL 50 |
| CATALOG NOTES | Suitable for use as service equipment when no more than 6 main disconnecting means are provided or when not used as lighting & appliance panelboard. Has notch for brhdk125 hold-down kit. |



Powering Business Worldwide

Product specifications

| | |
|-----------------------------|--|
| SPECIAL FEATURES | No feed-thru lugs, includes BREQS125 hold-down screw |
| TYPE | Main lug |
| AMPERAGE RATING | 200 A |
| BUS MATERIAL | Aluminum |
| COVER | Cover included |
| MAIN CIRCUIT BREAKER | BWH |
| MOUNTING | Combination |
| NUMBER OF CIRCUITS | 24 |
| NUMBER OF SPACES | 12 |
| PHASE | Single-phase |
| USED WITH | Type BR 1-inch breakers |
| VOLTAGE RATING | 120/240V |
| WIRE SIZE | #1 AWG-300 kcmil Cu/Al |
| BOX SIZE | B2 |
| ENCLOSURE | NEMA 1 |
| ENCLOSURE MATERIAL | Metallic |
| INTERRUPT RATING | 25 kAIC |
| NUMBER OF WIRES | 3 |

Resources

| | |
|-------------------------------|--|
| CATALOGS | Residential and Light Commercial, Loadcenters and Circuit Breakers, Volume 1 Tab 1 |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - BR1224L200 |
| WARRANTY GUIDES | Eaton type BR circuit breaker limited warranty June 2024 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.