

Specifications



Eaton S611D242N3S

S611 Soft Starter, Frame D, 242A, 200 hp, 480V, 120-242 FLA, 108-132V operating, #22-12 AWG, 1 conductor, Vertical mounting, 2 Slots, FDC circuit breaker, Class RK5/K5/J Fuse

General specifications

PRODUCT NAME	Eaton S811+/S801+ soft starter
CATALOG NUMBER	S611D242N3S
UPC	786685480367
PRODUCT LENGTH/DEPTH	8.37 in
PRODUCT HEIGHT	20.83 in
PRODUCT WIDTH	11.58 in
PRODUCT WEIGHT	38 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	IEC 60947-4-2 UL Listed CSA file No. 3211-06 IEC 60947-2 UL 1077 CSA Std. C22.2 No.235



Powering Business Worldwide

Product specifications

AMPERAGE RATING	242A
HORSEPOWER	200 hp
PHASE	Three-phase
TYPE	Soft starter
USER INTERFACE	LCD
VOLTAGE RATING	480 V
FREQUENCY RATING	47-63 Hz
FUSE SIZE	Class J Class K5 Class RK5
CIRCUIT BREAKER TYPE	FDC
FRAME SIZE	D
NUMBER OF CONDUCTORS	1
OPERATING TEMPERATURE - MAX	50 °C
FULL LOAD CURRENT RANGE	120-242 FLA
OPERATING VOLTAGE	108-132 V
WIRE SIZE	#22-12 AWG
NUMBER OF SLOTS	2
MOUNTING METHOD	Vertical
OPERATING TEMPERATURE - MIN	-20 °C

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1 Product Range Catalog Drives Engineering
MULTIMEDIA	Soft starter DS7 up to 200 A Soft Starter DS7 up to 32 A Soft Starter Product Family Overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S611D242N3S
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

