

Specifications



Photo is representative



Eaton XTCR040D11F

Eaton XT IEC contactor, 40A, Top-mounted, 230 Vac, 50 Hz, 1NO-1NC, 40A, Frame D, 55 mm, 50 Hz, 3, 7.5/ 10, 15, 30, 40 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Reversing, , Screw terminals, Full voltage reversing contactor

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCR040D11F
UPC	782116885800
PRODUCT LENGTH/DEPTH	6.5 in
PRODUCT HEIGHT	6 in
PRODUCT WIDTH	9.5 in
PRODUCT WEIGHT	4.7 lb
WARRANTY	1 year
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60947 CSA Certified EN 60947 UL Listed
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Product specifications

AMPERAGE RATING	40A
HP RATING - MAX	3, 7.5/ 10, 15, 30, 40 hp (1/3PH @115,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage reversing contactor
FREQUENCY RATING	50 Hz
FRAME SIZE	55 mm
TERMINALS	Screw terminals
COIL	230 Vac, 50 Hz
COIL VOLTAGE	230 Vac, 50 Hz
CONTACT CONFIGURATION	1 NO, 1 NC
CONTINUOUS AMPERE RATING	40 A
SERIES	XT IEC
OPERATION	Reversing

Resources

CATALOGS

[Motor Control and
Protection, IEC Contactors
and Starters, Volume 5,
Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet -
XTCR040D11F](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the
latest product and support
information.

