

Specifications



Photo is representative

Eaton T48M11S4516

Eaton General purpose ventilated transformer, DS-3 (1-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 120/240V, 150°C rise, 45 kVA, 16

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	T48M11S4516
UPC	786680210518
PRODUCT LENGTH/DEPTH	23.84 in
PRODUCT HEIGHT	42.03 in
PRODUCT WIDTH	24.22 in
PRODUCT WEIGHT	584 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Aluminum
ENCLOSURE	NEMA 2
FRAME	819
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry type distribution, ventilated transformer
WIRING CONNECTION	262F

Miscellaneous

WEATHERSHIELD	WS16
----------------------	------

Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	45 kVA

Resources

	Eaton's high-efficiency dry-type transformers
BROCHURES	Eaton's low-voltage dry-type distribution transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T48M11S4516

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.