

# Specifications



## Eaton TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

### General specifications

|                      |  |
|----------------------|--|
| PRODUCT NAME         | Eaton TR timing relay  |
| CATALOG NUMBER       | TRL07  |
| UPC                  | 786685313580   |
| PRODUCT LENGTH/DEPTH | 2.56 in  |
| PRODUCT HEIGHT       | 3.43 in  |
| PRODUCT WIDTH        | 0.69 in  |
| PRODUCT WEIGHT       | 0.16 lb  |
| WARRANTY             | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| COMPLIANCES          | TUV<br>CE Marked   |
| CERTIFICATIONS       | cULus Listed<br>CSA Certified  |



## Product specifications

|                              |                            |
|------------------------------|----------------------------|
| <b>FREQUENCY RATING</b>      | 50-60 Hz                   |
| <b>ENCLOSURE</b>             | IP40                       |
| <b>ENCLOSURE MATERIAL</b>    | Self-extinguishing plastic |
| <b>CONTACT CONFIGURATION</b> | SPDT                       |
| <b>TIME DELAY</b>            | 0.05 seconds-100 hours     |
| <b>SERIES</b>                | TR                         |

**FUNCTIONS**

Single shot leading or trailing edge voltage controlled and control input  
ON delay control signal start  
ON/OFF delay  
Trailing edge OFF  
Power triggered  
Flasher-pause first

**INPUT VOLTAGE** 24-240 Vac/dc

**MOUNTING METHOD** Compact DIN rail

## Resources

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - TRL07](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

