

Specifications



Photo is representative



Eaton GDA-1.6A

Eaton GDA Series Fast-acting fuse 1.60A, 250 Vac, 32 Vdc (self certified), GDA-1-6A

General specifications

PRODUCT NAME	Eaton Bussmann series GDA fast-acting fuse
CATALOG NUMBER	GDA-1.6A
UPC	051712431316
PRODUCT LENGTH/DEPTH	5.2 mm
PRODUCT HEIGHT	20 mm
PRODUCT WIDTH	5.2 mm
PRODUCT WEIGHT	1.02 g
COMPLIANCES	CCC Marked CE Marked
CERTIFICATIONS	VDE
CATALOG NOTES	High breaking capacity
GLOBAL CATALOG	GDA-1.6A



Powering Business Worldwide

Product specifications

AMPERAGE RATING	1.60 A
FREQUENCY RATING - MAX	50 Hz
FREQUENCY RATING - MIN	50 Hz
MELTING (I2T)	Typical: 0.748 A
RESISTANCE	0.113 ohms DC cold
VOLTAGE DROP	239 mV typical
INTERRUPT RATING	1.5 kAIC at 250 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
MATERIAL	Ceramic tube Nickel-plated brass end cap construction
QUANTITY	5
VOLTAGE RATING	250 Vac, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - GDA-1.6A](#)

[Eaton GDA fast-acting fuse data sheet](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

