

# Specifications



## Eaton XTMCXFA31

Miniature Contactor Accessory - Auxiliary Contact, Four-pole, Screw terminals, 3NO-1NC contact configuration, 10A conventional thermal rating, Front mounting, used with XTRM miniature control relays

### General specifications

<b>PRODUCT NAME</b>	Eaton motor control auxiliary contact
<b>CATALOG NUMBER</b>	XTMCXFA31
<b>EAN</b>	4015080489122
<b>PRODUCT LENGTH/DEPTH</b>	1.5 in
<b>PRODUCT HEIGHT</b>	1.5 in
<b>PRODUCT WIDTH</b>	2 in
<b>PRODUCT WEIGHT</b>	0.1 lb
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	ATEX Compliant CE Marked CCC Marked
<b>CERTIFICATIONS</b>	IEC 60947 EN 60947 UL Listed CSA Certified
<b>CATALOG NOTES</b>	Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.
<b>GLOBAL CATALOG</b>	XTMCXFA31



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	XTRM miniature control relays
<b>NUMBER OF POLES</b>	Four-pole
<b>TYPE</b>	Miniature Contactor Accessory - Auxiliary Contact
<b>TERMINALS</b>	Screw
<b>CONTACT CONFIGURATION</b>	3 NO-1 NC
<b>MOUNTING METHOD</b>	Front
<b>SPECIAL FEATURES</b>	Used with XTRM miniature control relays
<b>CONVENTIONAL THERMAL CURRENT</b>	10A
<b>QUANTITY</b>	5

## Resources

CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTMCXFA31</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

