

Specifications



Photo is representative

Eaton XTCE115G00B

Eaton XT IEC contactor, 115A, 190 Vac 50 Hz, 240 Vac 60 Hz, 0NO-0NC, 115A, Frame G, 90 mm, 50-60 Hz, 10, 25, 25/40, 50, 100, 100 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE115G00B
EAN	4015082395483
PRODUCT LENGTH/DEPTH	6.2992126 in
PRODUCT HEIGHT	6.69291339 in
PRODUCT WIDTH	4.37007874 in
PRODUCT WEIGHT	0.5070632 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Product specifications

AMPERAGE RATING	115A
HP RATING - MAX	10, 25, 25/ 40, 50, 100, 100 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	90 mm
TERMINALS	Screw terminals
COIL VOLTAGE	190-240 Vac, 50/60 Hz
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	115 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS

[Motor Control and
Protection, IEC Contactors
and Starters, Volume 5,
Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet -
XTCE115G00B](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the
latest product and support
information.

