

Specifications



Photo is representative



Eaton S20L11B15CUSS

Eaton General purpose encapsulated transformer, EP, copper, NEMA 3R, 182, 60 Hz, single-phase, 240 V, 480 V, 120/240 V, 2 at -5% FCBN X 4 at -2.5% FCBN, 80 °C rise, 15 KVA, indoor-outdoor, 23A

General specifications

PRODUCT NAME	Eaton General purpose encapsulated transformer
CATALOG NUMBER	S20L11B15CUSS
UPC	786680071638
PRODUCT LENGTH/DEPTH	14.12 in
PRODUCT HEIGHT	23.31 in
PRODUCT WIDTH	16.35 in
PRODUCT WEIGHT	429 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed
CATALOG NOTES	Grade 304 stainless steel enclosure

Physical Attributes	
COIL MATERIAL	Copper
DESIGN	EP
ENCLOSURE	NEMA 3R
FRAME	182
TAP SIZE	2 at -5% FCBN x 4 at -2.5% FCBN
TYPE	General-Purpose Encapsulated Transformer
WIRING CONNECTION	23A

Miscellaneous	
WEATHERSHIELD	Indoor-Outdoor

Performance Ratings	
FREQUENCY RATING	60 Hz
PHASE	Single-phase
PRIMARY VOLTAGE	240 V, 480 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	80 °C rise
VOLT AMPERE RATING	15 kVA

Resources	
CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S20L11B15CUSS

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

