

# Specifications



Photo is representative

## Eaton S20N11P51SS4X

Eaton General purpose encapsulated transformer, EP, copper, NEMA 4X, 57P4X, 60 Hz, 180C, 0.50 kVA, 0.5 kVA, wall mount, single-phase, 240 V, 480 V, 120/240 V, NEMA ST-20, None, 115 °C rise, 0.5 KVA, indoor-outdoor, 3A

### General specifications

<b>PRODUCT NAME</b>	Eaton General purpose encapsulated transformer
<b>CATALOG NUMBER</b>	S20N11P51SS4X
<b>UPC</b>	786680115929
<b>PRODUCT LENGTH/DEPTH</b>	6.6 in
<b>PRODUCT HEIGHT</b>	6.58 in
<b>PRODUCT WIDTH</b>	4.75 in
<b>PRODUCT WEIGHT</b>	14 lb
<b>WARRANTY</b>	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>COMPLIANCES</b>	Not Applicable
<b>CERTIFICATIONS</b>	UL Listed
<b>CATALOG NOTES</b>	NEMA 4X Grade 304 stainless steel enclosure.



Powering Business Worldwide

## Physical Attributes

<b>COIL MATERIAL</b>	Copper
<b>DESIGN</b>	EP
<b>ENCLOSURE</b>	NEMA 4X
<b>FRAME</b>	57P4X
<b>INSULATION</b>	180 °C
<b>MOUNTING</b>	Wall Mount
<b>TAP SIZE</b>	None
<b>TYPE</b>	General-purpose encapsulated transformer
<b>WIRING CONNECTION</b>	3A

## Miscellaneous

<b>SPECIAL FEATURES</b>	304SS NEMA 4X Enclosure
<b>WEATHERSHIELD</b>	Indoor-Outdoor

## Performance Ratings

<b>FREQUENCY RATING</b>	60 Hz
<b>KVA RATING</b>	0.50 kVA
<b>KVA</b>	0.5 kVA
<b>PHASE</b>	Single-phase
<b>PRIMARY VOLTAGE</b>	240 V, 480 V
<b>SECONDARY VOLTAGE</b>	120/240 V
<b>SOUND LEVEL</b>	NEMA ST-20
<b>TEMPERATURE RISE</b>	115 °C rise
<b>VOLT AMPERE RATING</b>	0.5 kVA

## Resources

CATALOGS	<a href="#">Commercial Distribution, Transformers, Volume 2, Tab 2</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - S20N11P51SS4X</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.