

Specifications



Eaton XTMCXFA20

Miniature Contactor Accessory - Auxiliary Contact, Two-pole, Screw terminals, 2NO contact configuration, 10A conventional thermal rating, Front mounting, used with XTRM miniature control relays

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton motor control auxiliary contact |
| CATALOG NUMBER | XTMCXFA20 |
| EAN | 4015080102083 |
| PRODUCT LENGTH/DEPTH | 1.5 in |
| PRODUCT HEIGHT | 2 in |
| PRODUCT WIDTH | 1.5 in |
| PRODUCT WEIGHT | 0.1 lb |
| WARRANTY | Not Applicable |
| COMPLIANCES | ATEX Compliant CE Marked CCC Marked |
| CERTIFICATIONS | IEC 60947 EN 60947 UL Listed CSA Certified |
| CATALOG NOTES | Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed. |
| GLOBAL CATALOG | XTMCXFA20 |



Powering Business Worldwide

Product specifications

| | |
|-------------------------------------|--|
| USED WITH | XTRM miniature control relays |
| NUMBER OF POLES | Two-pole |
| TYPE | Miniature Contactor Accessory - Auxiliary Contact |
| TERMINALS | Screw |
| CONTACT CONFIGURATION | 2 NO |
| MOUNTING METHOD | Front |
| CONVENTIONAL THERMAL CURRENT | 10A |
| QUANTITY | 5 |

Resources

| | |
|-------------------------------|--|
| CATALOGS | Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1 |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - XTMCXFA20 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

