

Specifications



Photo is representative

Eaton ACE10 60

Eaton Crouse-Hinds series ACE10 variable frequency drive, J disconnect fuse type, ABB ACS880-M04 Series drive, Size 2 enclosure, 82A input, 60 HP, Copper-free aluminum, 100A max. disconnect rating, 81A max. output, T4A, 45 kW

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series ACE10 variable frequency drive
CATALOG NUMBER	ACE10 60
UPC	662276247086
PRODUCT LENGTH/DEPTH	46.31 in
PRODUCT HEIGHT	15.74 in
PRODUCT WIDTH	25.15 in
PRODUCT WEIGHT	1150 lb

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2

Product specifications

DRIVE TYPE	ABB ACS880-M04 Series
HORSEPOWER	60 hp
WATTAGE	45 kW
DISCONNECT RATING - MAX	100A
DISCONNECT FUSE TYPE	J
ENCLOSURE SIZE	Size 2
INPUT CURRENT	82 A
OUTPUT CURRENT - MAX	81 A
TEMPERATURE RATING	T4A
MATERIAL	Copper-free aluminum

Resources

BROCHURES	ACE10 Series Explosionproof Variable Frequency Drives brochure
CATALOGS	ACE10 Series Explosionproof Variable Frequency Drives catalog page
CERTIFICATION REPORTS	ACE10 Explosionproof Variable Frequency Drives Canadian certification (pending) ACE10 Explosionproof Variable Frequency Drives UL certification
INSTALLATION INSTRUCTIONS	IF 1689 - ACE Variable Frequency Drive System IF 1616 - Flange Gasket Replacement Kit IF 1619 - ACE10 Variable Frequency Drive System
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - ACE10 60 ACE Series Explosionproof Variable Frequency Drives

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

