

Specifications



Photo is representative



Eaton V48M28E30CUEE

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 150°C rise [E], 30 kVA, Copper windings, EE

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	V48M28E30CUEE
UPC	786680039430
PRODUCT LENGTH/DEPTH	16.5 in
PRODUCT HEIGHT	30 in
PRODUCT WIDTH	23 in
PRODUCT WEIGHT	331 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient



Powering Business Worldwide

Physical Attributes	
COIL MATERIAL	Copper
FRAME	912B
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous	
WEATHERSHIELD	WS38

Performance Ratings	
FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	208 Y/120 V
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	30 kVA

Resources	
CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - V48M28E30CUEE

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

