

Specifications



Photo is representative



Eaton V48M28F75

Eaton General-Purpose Transformer, Dry Type Distribution, DT-3, Three-phase, PV: 480V, Taps: 2 at +2.5% FCAN, 4 at -2.5% FCBN, SV: 208Y/120V, 115°C, 75 kVA, Al windings , Frame: 914D, uses WS39

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
---------------------	--

CATALOG NUMBER	V48M28F75
-----------------------	-----------

UPC	786680036132
------------	--------------

PRODUCT LENGTH/DEPTH	22 in
-----------------------------	-------

PRODUCT HEIGHT	32.02 in
-----------------------	----------

PRODUCT WIDTH	29 in
----------------------	-------

PRODUCT WEIGHT	510 lb
-----------------------	--------

WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
-----------------	--

CERTIFICATIONS	UL Listed
-----------------------	-----------



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Aluminum
DESIGN	DT-3
FRAME	914D
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous

WEATHERSHIELD	WS39
----------------------	------

Performance Ratings

FREQUENCY RATING	60 Hz
KVA RATING	75 kVA
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	208Y/120 V
TEMPERATURE RISE	115 °C rise

Resources

CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - V48M28F75

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.