

(!) Discontinued

# Modbus SL communication interface module - 24 V DC

TRV00210

Discontinued on: Oct 8, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range of Product	NSX400630 MasterPact NT NS1600b3200 PowerPact P PowerPact J NS630b1600 PowerPact L MasterPact NW PowerPact R NSX100250 PowerPact H
Device short name	Modbus SL communication interface module
Product or Component Type	Interface module
Range compatibility	ComPact ComPact NS630b1600 Masterpact MasterPact NT ComPact ComPact NS1600b3200 Masterpact MasterPact NW ComPact ComPact NSX PowerPact PowerPact P PowerPact PowerPact L PowerPact PowerPact J PowerPact PowerPact H
Offer type	C4 C5
Product Compatibility	Compact NSX100250 Compact NS1600b3200 Compact NSX400630 Compact NS630b1600

### Complementary

,	
Communication network type	Universal Logic Plug 2-port RJ45 Modbus, Modbus Serial line slave 9.638.4 kbauds screw terminal block
Mounting Mode	By clips
Mounting Support	35 mm DIN rail
[Us] rated supply voltage	24 V DC - 2010 %
Maximum supply current	3 A
Current consumption	21 mA
Connections - Terminals	Screw terminal block
Product Certifications	CE CSA UL

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Standards	UL 508 EN/IEC 60947-1 CSA C22.2 No 14-05 CSA C22.2 No 0-M91
Height	3.5 in (89 mm)
Width	0.7 in (18 mm)
Depth	2.8 in (72 mm)
Net Weight	3.2 oz (90 g)
Accessory / separate part category	Spare part Compact NS630b1600 Spare part Compact NS1600b3200

### **Environment**

IP Degree of Protection	Connectors IP2X Other parts IP3x IP4X
Relative humidity	585 %
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Ambient Air Temperature for Operation	-4158 °F (-2070 °C)
Pollution degree	3
Flame retardance	V0 conforming to UL 94 V0 conforming to IEC 60947-1 V0 conforming to IEC 60695-2-11
Shock resistance	1000 m/s²
Vibration frequency	58.4 Hz

# Ordering and shipping details

Category	US10NET01081
Discount Schedule	ONET
GTIN	00785901023791
Returnability	No
Country of origin	FR

## **Packing Units**

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

## **Contractual warranty**

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

#### **Use Better**

#### 

EU RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)