

Specifications



Photo is representative



Eaton S20K11E07CU

Eaton General purpose encapsulated transformer, EP, copper, NEMA 3R, 178, 60 Hz, single-phase, 240 V, 480 V, 120/240 V, 1 at -10% FCBN X 2 at -5% FCBN, 115 °C rise, 7.5 KVA, indoor-outdoor, 21A

General specifications

PRODUCT NAME	Eaton General purpose encapsulated transformer
CATALOG NUMBER	S20K11E07CU
UPC	786680065064
PRODUCT LENGTH/DEPTH	9.89 in
PRODUCT HEIGHT	16 in
PRODUCT WIDTH	10.38 in
PRODUCT WEIGHT	139 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Copper
DESIGN	EP
ENCLOSURE	NEMA 3R
FRAME	178
TAP SIZE	1 at -10% FCBN x 2 at -5% FCBN
TYPE	General-Purpose Encapsulated Transformer
WIRING CONNECTION	21A

Miscellaneous

SPECIAL FEATURES	Electrostatically shielded
WEATHERSHIELD	Indoor-Outdoor

Performance Ratings

FREQUENCY RATING	60 Hz
PHASE	Single-phase
PRIMARY VOLTAGE	240 V, 480 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	115 °C rise
VOLT AMPERE RATING	7.5 kVA

Resources

CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S20K11E07CU

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.