

# Specifications



Photo is representative

## Eaton XTCE040D00TD

Eaton XT IEC contactor, 40A, 24-27 Vdc, 0NO-0NC, 40A, Frame D, 55 mm, 3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC contactor
<b>CATALOG NUMBER</b>	XTCE040D00TD
<b>EAN</b>	4015082777807
<b>PRODUCT LENGTH/DEPTH</b>	2.25 in
<b>PRODUCT HEIGHT</b>	6 in
<b>PRODUCT WIDTH</b>	5 in
<b>PRODUCT WEIGHT</b>	2.4 lb
<b>COMPLIANCES</b>	RoHS Compliant CE Marked
<b>CERTIFICATIONS</b>	UL Listed CSA Certified IEC 60947 EN 60947
<b>CATALOG NOTES</b>	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	40A
<b>HP RATING - MAX</b>	3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH @115,200,230/200,230,460,575 V)
<b>NUMBER OF POLES</b>	Three-pole
<b>TYPE</b>	Full voltage non-reversing contactor
<b>FRAME SIZE</b>	55 mm
<b>TERMINALS</b>	Screw terminals
<b>COIL</b>	24 Vdc
<b>COIL VOLTAGE</b>	24-27 Vdc
<b>CONTACT CONFIGURATION</b>	0 NO, 0 NC
<b>CONTINUOUS AMPERE RATING</b>	40 A
<b>SERIES</b>	XT IEC
<b>OPERATION</b>	Non-reversing

## Resources

CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTCE040D00TD</a>
WARRANTY GUIDES	<a href="#">Selling Policy 25-000 - Distribution and Control Products and Services</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

