

# Specifications



## Eaton XTRM10A22A

XT IEC Miniature Control Relay, Screw terminals, 45 mm - mini Frame size, 2NO-2NC contact configuration, 110V 50 Hz, 120V 60 Hz coil, 10A conventional thermal rating, 6A at 220/230/240V; 3A at 380/400/415V rated operational voltage



### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC control relay
<b>CATALOG NUMBER</b>	XTRM10A22A
<b>EAN</b>	4015080517740
<b>PRODUCT LENGTH/DEPTH</b>	2.5 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	2.5 in
<b>PRODUCT WEIGHT</b>	0.3 lb
<b>CERTIFICATIONS</b>	UL Listed
<b>CATALOG NOTES</b>	0

## Product specifications

<b>TYPE</b>	Control relay
<b>FRAME SIZE</b>	45 mm - mini
<b>COIL VOLTAGE</b>	110-120 Vac, 50/60 Hz
<b>CONTACT CONFIGURATION</b>	2 NO, 2 NC

## Resources

### CATALOGS

[Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1](#)

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTRM10A22A](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

