

# Specifications



Photo is representative



## Eaton XTMC6A10TD

Eaton XT IEC mini contactor, 6.60A, 24 Vdc, 1NO, 20A, 45 mm mini, 0.25, 0.75, 1/ 1.5, 2, 3, 3 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing mini contactor

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC mini contactor
<b>CATALOG NUMBER</b>	XTMC6A10TD
<b>EAN</b>	4015080516439
<b>PRODUCT LENGTH/DEPTH</b>	1.79 in
<b>PRODUCT HEIGHT</b>	2.28 in
<b>PRODUCT WIDTH</b>	1.44 in
<b>PRODUCT WEIGHT</b>	0.4 lb
<b>COMPLIANCES</b>	RoHS Compliant CE Marked
<b>CERTIFICATIONS</b>	UL Listed CSA Certified IEC 60947 EN 60947
<b>CATALOG NOTES</b>	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

## Product specifications

<b>AMPERAGE RATING</b>	6.60A
<b>HP RATING - MAX</b>	0.25, 0.75, 1/ 1.5, 2, 3, 3 hp (1/3PH @115,200,230/200,230,460,575 V)
<b>NUMBER OF POLES</b>	Three-pole
<b>TYPE</b>	Full voltage non-reversing mini contactor
<b>FRAME SIZE</b>	45 mm - mini
<b>TERMINALS</b>	Screw terminals
<b>COIL VOLTAGE</b>	24 Vdc
<b>CONTACT CONFIGURATION</b>	1 NO
<b>CONTINUOUS AMPERE RATING</b>	20 A
<b>SERIES</b>	XT IEC
<b>OPERATION</b>	Non-reversing

## Resources

<b>CATALOGS</b>	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
<b>MULTIMEDIA</b>	<a href="#">Contactors Explained</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">S1. E4. Ask the Experts - NEMA, IEC and DP contactors</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - XTMC6A10TD</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

