



SIMATIC ET 200SP HA, 5 TM covers, 22.5 mm, for protection of I/O empty slots

| General information                  |                                |          |                |
|--------------------------------------|--------------------------------|----------|----------------|
| Product type designation             | TM cover                       |          |                |
| Ambient conditions                   |                                |          |                |
| Ambient temperature during operation |                                |          |                |
| • min.                               | -40 °C                         |          |                |
| • max.                               | 70 °C                          |          |                |
| • horizontal installation, min.      | -40 °C                         |          |                |
| • horizontal installation, max.      | 70 °C                          |          |                |
| • vertical installation, min.        | -40 °C                         |          |                |
| • vertical installation, max.        | 70 °C                          |          |                |
| Dimensions                           |                                |          |                |
| Width                                | 22.5 mm                        |          |                |
| Height                               | 115 mm                         |          |                |
| Depth                                | 69 mm                          |          |                |
| Weights                              |                                |          |                |
| Weight, approx.                      | 40 g                           |          |                |
| Classifications                      |                                |          |                |
|                                      |                                | Version  | Classification |
|                                      | eClass                         | 14       | 27-24-26-92    |
|                                      | eClass                         | 12       | 27-24-26-92    |
|                                      | eClass                         | 9.1      | 27-24-26-92    |
|                                      | eClass                         | 9        | 27-24-26-92    |
|                                      | eClass                         | 8        | 27-24-26-92    |
|                                      | eClass                         | 7.1      | 27-24-26-92    |
|                                      | eClass                         | 6        | 27-24-26-92    |
|                                      | ETIM                           | 9        | EC002584       |
|                                      | ETIM                           | 8        | EC002584       |
| ETIM                                 | 7                              | EC002584 |                |
| Approvals / Certificates             |                                |          |                |
| General Product Ap-<br>proval        | For use in hazardous locations |          |                |



