



*** Spare part *** SIMATIC DP, Electronics module 2 AI U High Feature f. ET200S, 15 mm width, Cycle time per module: 0.5 ms, +/-10V; 15 bit+sign, +/-5 V; 15 bit+sign, 1..5 V; 15 bit, Operational limit +/-0.1% with SF LED (group fault)

General information	
Product function	
• Isochronous mode	Yes
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	55 mA
from backplane bus 3.3 V DC, max.	10 mA
output voltage / header	
supply voltage of the transmitters / header	
• present	No
Power loss	
Power loss, typ.	0.85 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous; 75 V for max. 1 ms
Cycle time (all channels) max.	0.5 ms; 0.5 ms for 2 channels without noise suppression, 18 / 21 ms per channel with noise suppression
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	800 kΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	800 kΩ
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	800 kΩ
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 0 to 5 V: 15 bit, ±10 V: 16 bit, ±5 V: 16 bit
• Integration time, parameterizable	Yes
• Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz / no
• Conversion time (per channel)	0.04 ms; Without noise suppression 17/20 ms per channel with error
Smoothing of measured values	

• parameterizable • Step: None • Step: low • Step: Medium • Step: High	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time																																							
	Yes; 1x																																							
	Yes; 4x																																							
	Yes; 16x																																							
	Yes; 32x																																							
Encoder																																								
Connection of signal encoders																																								
• for voltage measurement	Yes																																							
Errors/accuracies																																								
Operational error limit in overall temperature range																																								
• Voltage, relative to input range, (+/-)	0.1 %; 0.2% without interference frequency suppression																																							
Basic error limit (operational limit at 25 °C)																																								
• Voltage, relative to input range, (+/-)	0.05 %; 0.1% without interference frequency suppression																																							
Interrupts/diagnostics/status information																																								
Alarms																																								
• Hardware interrupt	Yes																																							
Diagnoses																																								
• Wire-break	Yes; Measuring range 1 to 5 V only																																							
• Group error	Yes																																							
• Overflow/underflow	Yes																																							
Diagnostics indication LED																																								
• Group error SF (red)	Yes																																							
Parameter																																								
Remark	12 bytes, 4 bytes in compatibility mode																																							
Group diagnostics	Disable / enable																																							
Overflow/underflow	Disable / enable																																							
Potential separation																																								
Potential separation analog inputs																																								
• between the channels	No; however, increased permissible potential difference between the inputs.																																							
• between the channels and backplane bus	Yes																																							
• Between the channels and load voltage L+	Yes																																							
Isolation																																								
Isolation tested with	500 V DC																																							
Dimensions																																								
Width	15 mm																																							
Height	81 mm																																							
Depth	52 mm																																							
Weights																																								
Weight, approx.	45 g																																							
Classifications																																								
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>14</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>12</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>9</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-26-01</td></tr><tr><td>ETIM</td><td>9</td><td>EC001596</td></tr><tr><td>ETIM</td><td>8</td><td>EC001596</td></tr><tr><td>ETIM</td><td>7</td><td>EC001596</td></tr><tr><td>IDEA</td><td>4</td><td>3562</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	14	27-24-26-01	eClass	12	27-24-26-01	eClass	9.1	27-24-26-01	eClass	9	27-24-26-01	eClass	8	27-24-26-01	eClass	7.1	27-24-26-01	eClass	6	27-24-26-01	ETIM	9	EC001596	ETIM	8	EC001596	ETIM	7	EC001596	IDEA	4	3562	UNSPSC	15	32-15-17-05
	Version	Classification																																						
eClass	14	27-24-26-01																																						
eClass	12	27-24-26-01																																						
eClass	9.1	27-24-26-01																																						
eClass	9	27-24-26-01																																						
eClass	8	27-24-26-01																																						
eClass	7.1	27-24-26-01																																						
eClass	6	27-24-26-01																																						
ETIM	9	EC001596																																						
ETIM	8	EC001596																																						
ETIM	7	EC001596																																						
IDEA	4	3562																																						
UNSPSC	15	32-15-17-05																																						
Approvals / Certificates																																								
General Product Approval																																								

[Manufacturer Declaration](#)



[Miscellaneous](#)



[Metrological Approval](#)

General Product Approval

EMV

For use in hazardous locations



[EM](#)



For use in hazardous locations

Marine / Shipping

[Miscellaneous](#)



[CCC-Ex](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

7/19/2024