SIEMENS

Data sheet 6ES7193-6BR00-0HM0



Figure similar

SIMATIC ET 200SP, BaseUnit M0 with 2 slots for accommodating R1-capable Interface module IM 155-6 PN R1 incl. server module

General information	
Product type designation	BU type M0
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
● Number of slots	2
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Dimensions	
Width	100 mm
Height	141 mm
Depth	29 mm
Weights	
Weight, approx.	142 g
Classifications	

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	9	EC001598
ETIM	8	EC001598

Subject to change without notice
© Copyright Siemens

	ETIM	7	EC001598

Approvals / Certificates

General Product Approval

CE EG-Konf. | UKCA | Manufacturer Declaration | KC | RCM | KC

For use in hazardous locations

UL | FM | CCC-Ex | ATEX | IECEx | Miscellaneous

Marine / Shipping

ABS | BUREAU VERITAS | DNV | Lloyd's Register LRS | NK / Nippon Kaiji Kyokai | RINA

Marine / Shipping

RMRS | CCS (China Classification Society)

last modified: 5/22/2024

Subject to change without notice
© Copyright Siemens