

Product data sheet

Specifications

SQUARE D



30mm Push Button, Types K, SK or KX, light module, white LED lamp, 120 VAC/VDC

9001KM38LW

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|---------------------------|---------------------------------------|
| Range of Product | Harmony 9001K Harmony 9001SK |
| Product or Component Type | Light module Light block |
| Device short name | 9001K |
| Bulb base | BA 9s |
| Light block supply | Direct via integral resistance 1.4 VA |

Complementary

| | |
|---------------------------|---------------------------------|
| Light source | LED (bulb included) |
| Light block colour | White |
| [Us] rated supply voltage | 120 V AC 50...60 Hz 120 V DC |

Environment

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) -40...70 °C (-40...158 °F) |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) -25...70 °C (-13...158 °F) |
| IP degree of protection | IP20 IEC 60529 |
| Standards | UL 508 CSA C22.2 No 14 EN/IEC 60947-5-4 EN/IEC 60947-5-1 EN/IEC 60947-1 JIS C 4520 JIS C 852 |
| Product Certifications | UL Listed CSA NEMA |
| Electrical shock protection class | Class II conforming to IEC 61140 |
| Vibration resistance | 7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CS121435 |
| Discount Schedule | 0CS1 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--------------------------|--------------|
| GTIN | 785901696490 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|-------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 1.89 in (4.8 cm) |
| Package 1 Width | 2.28 in (5.8 cm) |
| Package 1 Length | 3.70 in (9.4 cm) |
| Package weight(Lbs) | 2.6 oz (72.6 g) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

|  Materials and Substances | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| SCIP Number | Ae0c4eb9-0bf8-40a4-851f-5c619f8e777d |
| REACH Regulation | REACH Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Use Again

|  Repack and remanufacture | |
|--|----|
| Take-back | No |