

# Product data sheet

Specifications

SQUARE D



30mm Push Button, Types K, SK or KX, light module, transformer, green 6V LED lamp, 110/120 VAC 50/60 Hz

9001KM1LG

Product availability: Non-Stock - Not normally stocked in distribution facility

## Main

Range of Product	Harmony 9001K Harmony 9001SK
Product or Component Type	Light module Light block
Device short name	9001K
Bulb base	BA 9s
Light block supply	Direct via integral transformer 6 V

## Complementary

Light source	LED (bulb included)
Light block colour	Green
[Us] rated supply voltage	120 V AC 60 Hz 110 V AC 50 Hz

## Environment

Protective treatment	TC
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C) -40...70 °C (-40...158 °F)
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C) -25...70 °C (-13...158 °F)
IP degree of protection	IP20 IEC 60529
Standards	UL 508 CSA C22.2 No 14 EN/IEC 60947-5-4 EN/IEC 60947-5-1 EN/IEC 60947-1 JIS C 4520 JIS C 852
Product Certifications	UL Listed CSA NEMA
Electrical shock protection class	Class II conforming to IEC 61140
Vibration resistance	7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

## Ordering and shipping details

Category	US10CS121435
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Discount Schedule</b>	0CS1
<b>GTIN</b>	785901816409
<b>Returnability</b>	No
<b>Country of origin</b>	MX

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	1.80 in (4.572 cm)
<b>Package 1 Width</b>	2.20 in (5.588 cm)
<b>Package 1 Length</b>	3.70 in (9.398 cm)
<b>Package weight(Lbs)</b>	5.280 oz (149.685 g)
<b>Unit Type of Package 2</b>	CAR
<b>Number of Units in Package 2</b>	16
<b>Package 2 Height</b>	5.80 in (14.732 cm)
<b>Package 2 Width</b>	5.80 in (14.732 cm)
<b>Package 2 Length</b>	15.70 in (39.878 cm)
<b>Package 2 Weight</b>	5.300 lb(US) (2.404 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ae0c4eb9-0bf9-40a4-851f-5c619f9be777d
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No