

Push-to-test pilot light, Harmony 9001K, metal, polycarbonate, domed, red, 30mm, LED red, 120V

9001KT38LRR9

## Main

Range of product	Harmony 9001K	
Product or component type	Push-to-test pilot light	
Device short name	K	

## Complementary

Bezel material	Metal
Mounting diameter	30 mm
Lens type	Domed plastic
Cap/operator or lens colour	Red
Light source	Red LED
Bulb base	BA 9s
Light block supply	Direct 120 V
Shape of screw head	Round
Light source	LED
Operating mode	Push-to-test
Lens type	Domed
[Us] rated supply voltage	120 V
Light source colour	Red
Contacts type and composition	1 C/O
Lens material	Polycarbonate
Size	30 mm

### **Environment**

Product certifications	CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR CE
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	6.1 cm

Package 1 Length	11.4 cm	
Package 1 Weight	181.4 a	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.

### **Use Again**

○ Repack and remanufacture		
Take-back	No	