

Product data sheet

Specifications



servo motor BMH, Lexium 32,
34.4Nm, 3800rpm, keyed shaft,
without brake, IP54, 128bit encoder

BMH2051P11A2A

Main

Device short name	BMH
Product or component type	Servo motor
Maximum mechanical speed	3800 rpm
Continuous stall torque	34.4 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 34.4 N.m for LXM32.D72N4 at 24 A, 480 V, three phase
Peak stall torque	103.4 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 103.4 N.m for LXM32.D72N4 at 24 A, 480 V, three phase
Nominal output power	5400 W for LXM32.D72N4 at 24 A, 400 V, three phase 5400 W for LXM32.D72N4 at 24 A, 480 V, three phase
Nominal torque	25.8 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 25.8 N.m for LXM32.D72N4 at 24 A, 480 V, three phase
Nominal speed	2000 rpm for LXM32.D72N4 at 24 A, 400 V, three phase 2000 rpm for LXM32.D72N4 at 24 A, 480 V, three phase
Product compatibility	LXM32.D72N4 at 400...480 V three phase
Shaft end	Keyed
IP degree of protection	IP54 standard
Speed feedback resolution	131072 points/turn
Holding brake	Without
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

Complementary

Range compatibility	Lexium 32
[Us] rated supply voltage	480 V
Network number of phases	Three phase
Continuous stall current	21.5 A
Continuous power	6.8 W
Maximum current Irms	78.1 A for LXM32.D72N4
Maximum permanent current	78.1 A
Second shaft	Without second shaft end
Shaft diameter	38 mm
Shaft length	80 mm
key width	70 mm
Feedback type	Single turn SinCos Hiperface

Motor flange size	205 mm
Number of motor stacks	1
Torque constant	1.6 N.m/A
Back emf constant	104 V/krpm at 120 °C
Number of motor poles	5.0
Rotor inertia	71.4 kg.cm ²
Stator resistance	0.3 Ohm at 20 °C
Stator inductance	2.95 mH at 20 °C
Stator electrical time constant	19.7 ms at 20 °C
Maximum radial force Fr	3730 N at 1000 rpm 2960 N at 2000 rpm 2580 N at 3000 rpm
Maximum axial force Fa	0.2 x Fr
type of cooling	Natural convection
Length	321 mm
Centring collar diameter	180 mm
centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Net weight	33 kg
Sizing reference	BMH2051P
Network number of phases	3
Accuracy error [angular]	1.4 °
Temperature copper hot	135 °C
Temperature magnet hot	100 °C
Temperature magnet rt	20 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	36.0 cm
Package 1 Width	31.0 cm
Package 1 Length	58.0 cm
Package 1 Weight	39.0 kg

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 5991

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number A7df881f-135f-4256-b8c2-ea55d4c9a151

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

PVC free Yes

Use Again

Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins