

Specifications



Photo is representative



Eaton XTCE225H22B

Eaton XT IEC contactor, 225 A, 190 Vac 50 Hz, 240 Vac 60 Hz, 2NO-2NC, 225A, Frame H, 140 mm, 50-60 Hz, 50, 75, 150, 200 hp (3PH at 200, 240, 480, 600 V), Three-pole

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE225H22B
EAN	4015081363254
PRODUCT LENGTH/DEPTH	15.24 cm
PRODUCT HEIGHT	19.05 cm
PRODUCT WIDTH	13.97 cm
PRODUCT WEIGHT	2.26 kg
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	225 A
HP RATING - MAX	50, 75, 150, 200 hp (3PH @200,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50-60 Hz
TERMINALS	Screw terminals
COIL VOLTAGE	190-240 Vac, 50-60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	225 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE225H22B

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.