

# Specifications



Photo is representative



## Eaton XTCEXFAC40

Contactor Accessory - Auxiliary Contact, Four-pole, Screw terminals, 4NO contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

### General specifications

<b>PRODUCT NAME</b>	Eaton motor control auxiliary contact
<b>CATALOG NUMBER</b>	XTCEXFAC40
<b>EAN</b>	4015082764289
<b>PRODUCT LENGTH/DEPTH</b>	1.5 in
<b>PRODUCT HEIGHT</b>	1.5 in
<b>PRODUCT WIDTH</b>	2.5 in
<b>PRODUCT WEIGHT</b>	0.1 lb
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	ATEX Compliant CE Marked CCC Marked
<b>CERTIFICATIONS</b>	IEC 60947 EN 60947 UL Listed CSA Certified
<b>CATALOG NOTES</b>	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.
<b>GLOBAL CATALOG</b>	XTCEXFAC40

## Product specifications

USED WITH	XTRE control relays
NUMBER OF POLES	Four-pole
TYPE	Contactor Accessory - Auxiliary Contact
TERMINALS	Screw
CONTACT CONFIGURATION	4 NO
MOUNTING METHOD	Front
RATED OPERATIONAL CURRENT	6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
CONVENTIONAL THERMAL CURRENT	16A
QUANTITY	5

## Resources

CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTCEXFAC40</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

