Specifications

Photo is representative

Eaton XTCE250L22A

Eaton XT IEC contactor, 250A, 110 Vdc 40 Hz, 250 Vdc 60 Hz, 2NO-2NC, 250A, Frame L, 140 mm, 40-60 Hz, 75, 100, 200, 250 hp (3PH @200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE250L22A
EAN	4015082082017
PRODUCT LENGTH/DEPTH	8.18897638 in
PRODUCT HEIGHT	7.08661417 in
PRODUCT WIDTH	5.51181102 in
PRODUCT WEIGHT	0.5070632 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Powering Business Worldwide

Product specifications

AMPERAGE RATING	250 A
HP RATING - MAX	75, 100, 200, 250 hp (3PH @200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	40-60 Hz
FRAME SIZE	140 mm
TERMINALS	Screw terminals
COIL VOLTAGE	110-250 Vdc
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	250 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE250L22A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.