

Specifications



Photo is representative



Eaton XTMC6A10T

Eaton XT IEC mini contactor, 6.60A, 24 Vac, 50-60 Hz, 1NO, 20A, 45 mm mini, 50-60 Hz, 0.25, 0.75, 1/ 1.5, 2, 3, 3 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing mini contactor

General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	XTMC6A10T
EAN	4015080515968
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	2.5 in
PRODUCT WEIGHT	0.3 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	6.60A
HP RATING - MAX	0.25, 0.75, 1/ 1.5, 2, 3, 3 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing mini contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	45 mm - mini
TERMINALS	Screw terminals
COIL VOLTAGE	24 Vac, 50-60 Hz
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	20 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTMC6A10T

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

