

Specifications



Photo is representative

Eaton XTCE150GS1TD

Eaton XT IEC contactor, 150A, Side-mounted, 24-27 Vdc, 1NO-1NC, 150A, Frame G, 90 mm, 10, 25, 30/ 40, 60, 125, 125 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE150GS1TD
UPC	786685365282
PRODUCT LENGTH/DEPTH	1 in
PRODUCT HEIGHT	1 in
PRODUCT WIDTH	1 in
PRODUCT WEIGHT	1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947



Powering Business Worldwide

Product specifications

AMPERAGE RATING	150A
HP RATING - MAX	10, 25, 30/ 40, 60, 125, 125 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FRAME SIZE	90 mm
TERMINALS	Screw terminals
COIL	24 Vdc
COIL VOLTAGE	24-27 Vdc
CONTACT CONFIGURATION	1 NO, 1 NC
CONTINUOUS AMPERE RATING	150 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE150GS1TD

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

