

Product data sheet

Specifications



REACTOR DRIVE LINE 3PH 1.5-2HP 208/230V T-1

RL00812

⚠ Discontinued on: Jun 15, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

⚠ Discontinued

Complementary

Line Rated Current	8 A
AWG gauge	AWG 22...AWG 14
Depth	6 in (152.4 mm)
Electrical Connection	Screw clamp terminal
Height	8 in (203.2 mm)
Permissible voltage	600 V AC
Net Weight	15 lb(US) (6.8 kg)
Protection Type	Harmonic distortion Overvoltage protection Current protection
Width	8 in (203.2 mm)

Environment

Product Certifications	UL listed file E180243 CE CSA LR29753
------------------------	---

Ordering and shipping details

Category	US1CP4C22062
Discount Schedule	CP4C
GTIN	785901142652
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.99 in (20.3 cm)
Package 1 Width	7.99 in (20.3 cm)
Package 1 Length	5.98 in (15.2 cm)
Package weight(Lbs)	13.0007 lb(US) (5.897 kg)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Warranty

18 months