

Specifications



Photo is representative

Eaton EVLLA5LC0-UNV1

Eaton Crouse-Hinds series Hazard-Gard EVLLA explosionproof LED light fixture, Cool white, 100W-150W HID equivalent, No guard, Shatter-resistant glass lens, 5000 lumens, 105 lm/W, Copper-free aluminum, No mounting module, 120-277 Vac, 59W

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Hazard-Gard EVLLA LED light fixture
CATALOG NUMBER	EVLLA5LC0-UNV1
UPC	662276950580
PRODUCT LENGTH/DEPTH	15.9 in
PRODUCT HEIGHT	11.97 in
PRODUCT WIDTH	15.9 in
PRODUCT WEIGHT	51.76 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class II, Division 1 Class III
NEMA RATING	4X
INGRESS PROTECTION (IP) RATINGS	IP66

Product specifications

LUMENS	5000
LUMENS PER WATT	105
COLOR TEMPERATURE	Cool white
MOUNTING METHOD	No mounting module
EQUIVALENT LUMINAIRE	100W-150W HID
GUARD TYPE	No guard
VOLTAGE RATING	120-277 Vac
FREQUENCY RATING	50/60 Hz
MATERIAL	Copper-free aluminum
LENS MATERIAL	Shatter-resistant glass
WATTAGE	59W
DIMMING	Dimmable driver
POWER FACTOR	> 0.90

Resources

	Crouse-Hinds series Global LED lighting portfolio
BROCHURES	Crouse-Hinds series Hazard-Gard EVLL LED brochure Crouse-Hinds series DLC approved lighting products
CATALOGS	Crouse-Hinds series Hazard-Gard EVLLA LED catalog page
CERTIFICATION REPORTS	Hazard-Gard EVLLA Explosionproof LED Light Fixtures Canadian certification Hazard-Gard EVLLA Explosionproof LED Light Fixtures UL certification
INSTALLATION INSTRUCTIONS	IF 1914 - EVLLA Hazard-Gard LED Luminaire Driver Replacement IF 1913 - EVLLA Hazard-Gard LED Luminaire
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EVLLA5LC0-UNV1 Hazard-Gard EVLL LED Explosionproof

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

