

Specifications



Photo is representative

Eaton ACE20 10

Eaton Crouse-Hinds series ACE20 variable frequency drive, J disconnect fuse type, Allen Bradley PowerFlex 700 Series drive, Size 2 enclosure, 12.5A input, 10 HP, Copper-free aluminum, 30A max. disconnect rating, 14A max. output, T4A, 7.5 kW

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series ACE20 variable frequency drive
CATALOG NUMBER	ACE20 10
UPC	662276468931
PRODUCT LENGTH/DEPTH	46.31 in
PRODUCT HEIGHT	15.69 in
PRODUCT WIDTH	25.15 in
PRODUCT WEIGHT	550 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2
NEMA RATING	3 4X 7

Product specifications

DRIVE TYPE	Allen Bradley PowerFlex 700® Series
HORSEPOWER	10 hp
WATTAGE	7.5 kW
DISCONNECT RATING - MAX	30A
DISCONNECT FUSE TYPE	J
ENCLOSURE SIZE	Size 2
INPUT CURRENT	12.5 A
OUTPUT CURRENT - MAX	14 A
TEMPERATURE RATING	T4A
MATERIAL	Copper-free aluminum

Resources

CATALOGS	ACE20 Series Explosionproof Variable Frequency Drives catalog page
CERTIFICATION REPORTS	ACE20 Explosionproof Variable Frequency Drives Canadian certification (pending) ACE20 Explosionproof Variable Frequency Drives UL certification
INSTALLATION INSTRUCTIONS	IF 1660 - ACE20 and ACE30 Variable Frequency Drive System
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - ACE20 10 ACE Series Explosionproof Variable Frequency Drives

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

