

Specifications



Eaton APX17L/UNV1 S903

Eaton Crouse-Hinds series Pauluhn Apex linear LED light fixture, 4-lamp T5HO, 50/60 Hz, LED, Polycarbonate lens, 17000 lm, 118 lm/W, Aluminum, PF > 0.90, 120-277 Vac, 127-250 Vdc, 144W

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Pauluhn Apex linear LED light fixture
CATALOG NUMBER	APX17L/UNV1 S903
UPC	662276618114
PRODUCT LENGTH/DEPTH	40.61 in
PRODUCT HEIGHT	6.39 in
PRODUCT WIDTH	7.66 in
PRODUCT WEIGHT	23.41 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Ordinary/Non-Hazardous Locations
STANDARDS TYPE	NEC/CEC
NEMA RATING	4X
INGRESS PROTECTION (IP) RATINGS	IP66

Product specifications

LAMP TYPE	LED
LUMENS	17000
LUMENS PER WATT	118
VOLTAGE RATING	120-277 Vac, 127-250 Vdc
FREQUENCY RATING	50/60 Hz
LENS MATERIAL	Polycarbonate
MATERIAL	Aluminum
WATTAGE	144W
EQUIVALENT LUMINAIRE	4-lamp T5HO
POWER FACTOR	> 0.90

Resources

[Crouse-Hinds series industrial LED lighting solutions](#)

[Crouse-Hinds series Global LED lighting portfolio](#)

BROCHURES

[Crouse-Hinds series Pauluhn Apex LED Linear brochure - food and beverage](#)

[Crouse-Hinds series Pauluhn Apex LED Linear brochure - industrial applications](#)

CATALOGS

[Crouse-Hinds series Pauluhn Apex LED Linear catalog page](#)

[Pauluhn Apex Industrial Linear LED Light Fixtures NSF certification](#)

[Champ Pro PFM LED, Pauluhn Apex Industrial LED, Industrial High Bay LED and Weatherproof LED Light Fixtures Canadian certification](#)

CERTIFICATION REPORTS

[Champ Pro PFM LED, Pauluhn Apex Industrial LED, Industrial High Bay LED and Weatherproof LED Light Fixtures UL certification](#)

INSTALLATION INSTRUCTIONS

[IF 1820 - Pauluhn Apex LED Linear](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - APX17L/UNV1 S903](#)

[Pauluhn APEX LED Linear](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

