

Product Specification Sheet

39921-6

UPC: 08593707386

UNSPSC: 31162104

Standard Qty: 1
Master Carton Qty: 6

Country of Origin: USA

#8 EZ Ancors™, White Plastic with #8 x 1" Screws, Phillips/Slotted, Includes #2-2" Hex Power Bit



Pro	oduct Attributes	Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	E-Z Ancor®	,
Application	Drywall, Horizontal	Buy American Act Compliant: No
Diameter	1/2"	RoHS Compliant: Yes
Length	1-5/8": 1" Screw	·
Head Type	Slot/Phil Pan Head	UL Compliant:
Point Type	Sheet Metal	UL Code:
Material	Nylon Anchor: Steel Screw	Drangaition 65
Finish	White Anchor: Zinc Screw	Proposition 65
Fixture Thickness	Max 3/4"	This product is in compliance with
Special Features	E-Z Ancor®Plastic: #8 Self Drilling Drywall Anchor Slot/Phil: #8 X 1" Slot/Phil Pan Head Sheet Metal Screw: #2-2" Phil Hex Power Bit	Prop65; it is not known to contain any chemicals associated with this regulation.
Size	#8 X 1-5/8"	
Screw Size	#8 X 1"	
Sub Brand	Cully	
Туре	Hollow Wall Anchor	
Application	Predrills precise hold in gypsum wall board. For 3/8", 1/2", or 5/8" wall board. One tool installation; requires only a Phillips screw driver. Removable	Minerallac Company Tel: 800-927-3293 Fax: 800-824-8942
Min Clearance behine Wall	1-5/8"	www.minerallac.com
Min Wall Thickness	3/8"	
Material	White Nylon Anchor. Zinc plated carbon steel screw	
Holding Weight`	50 lbs	
Max Fixure Thickness	3/4"	
Disclaimer	Nor for Life Safety or Overhead Applications	
Anchor Size	1/2" x 1-5/8"	
Screw Size and Type	#8 x 1" Pan Head Phillips/Sotted Sheet Metal Screw	









Product Specification Sheet

39921-6

UPC: 08593707386

UNSPSC: 31162104

Standard Qty: 1

Master Carton Qty: 6

Country of Origin: USA

#8 EZ Ancors™, White Plastic with #8 x 1" Screws, Phillips/Slotted, Includes #2-2" Hex Power Bit



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence,

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.











