

**39913**

UPC: 08593739913


UNSPSC: 31162103

Standard Qty: 1

Master Carton Qty: 18

Country of Origin: CHINA

100 ct Zinc Anchor Kit with Wafer Head Screws, included 1/4" carbide bit



## Product Attributes

|                         |                                                                                                                   |
|-------------------------|-------------------------------------------------------------------------------------------------------------------|
| Brand Name              | Minerallac                                                                                                        |
| Sub Brand               | Cully                                                                                                             |
| Application             | The conical plastic anchor is a light-duty part that can be used in drywall, concrete, and hollow block or brick. |
| Length                  | 1.000"                                                                                                            |
| Head Type               | Wafer                                                                                                             |
| Material                | Engineered Plastic                                                                                                |
| Size                    | #10 – #12                                                                                                         |
| Minimum Embedment Depth | 1.000"                                                                                                            |
| Drill Size              | 1/4"                                                                                                              |
| Screw Size              | #12 x 1.000"                                                                                                      |
| Tension Strength        | In 4,000 PSI Concrete: 550 LB; in hollow brick: 350 LB; in solid red brick: 280                                   |
| Shear Strength          | In 4,000 PSI Concrete: 350 LB; in hollow brick: 280 LB; in solid red brick: 320                                   |
| Type                    | Self Drilling Zinc Drywall Anchor                                                                                 |
| Application             | Drywall Anchor#8 Zinc Self Drilling Drywall Anchor W Wafer Head Screws                                            |
| Size                    | #8 x 1-5/8" IN                                                                                                    |
| Diameter                | 1/2" IN                                                                                                           |
| Length                  | 1-5/8"                                                                                                            |
| Minimum Embedment Depth | 1-5/8"                                                                                                            |
| Material                | Zinc                                                                                                              |
| Finish                  | Zinc Plated                                                                                                       |
| Tension Strength        | Holding Weight 50lbs in 1/2" Drywall                                                                              |
| Fixture Thickness       | Max 3/4"                                                                                                          |
| Disclaimer              | Not for Life Safety or Overhead Applications                                                                      |

## Compliance Information

Buy America Act Compliant: No  
 Buy American Act Compliant: No  
 RoHS Compliant: Yes  
 UL Compliant:  
 UL Code:

## Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

## Minerallac Company

Tel: 800-927-3293  
 Fax: 800-824-8942  
[www.minerallac.com](http://www.minerallac.com)

**39913**


UPC: 08593739913

UNSPSC: 31162103

Standard Qty: 1

Master Carton Qty: 18

Country of Origin: CHINA

100 ct Zinc Anchor Kit with Wafer Head Screws, included 1/4"  
carbide bit

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.